

# WORKSHOP CUTTERS

## HAND OPERATED

EM 4



EM 4 DC



### Technical data

	EM 4	EM 4 DC
Production SAE R13 and SAE R15	1 1/4"	-
Workshop SAE R13 and SAE R15*	1 1/2"	1 1/4"
SAE R12	2"	1 1/2"
Industrial	2"	2"
Max. outside	Ø 80 mm	Ø 75 mm
Noise level	90 dBA	93 dBA
Brake motor	✓	-
Suction connection	Ø 80 mm	Ø 40 mm
Drive	3 kW 3 VAC	2,0 kW 12VDC
Cutting blade	TM C 275 x 3 x 30	TM C 250 x 2 x 40
L x W x H (mm)	700 x 510 x 700	740 x 365 x 610
Weight	60 kg	29 kg
Accessories		
TU Table	✓	✓
Suction device**	✓	✓
UVC 36 Adapter (230 Volt)	777.056	777.153
UVC 100 Adapter	330.082.3	330.083.3
Hose measuring tool	✓	✓
Foot for UMS 4 (840mm height)	-	-
Hose guides 2000mm (JHG 14)	✓	-

\* With special cutting blade. \* Adapter needed.

### Optional Extras (See page 463)



The best return on Investment since 1972.



### TMC, TMG and TM

High-quality cutting blades:  
TM C, TM G and TM.



### TMC

Lasts 7 times longer, cuts twice as fast, generates less smoke, less debris in the hose and less heat. Reduces the risk of separation of the rubber from the wire.