



The UNIFLEX KS 6, KS 8 and KS 10 are designed for precision crimping and calibration.



KS 6, KS 8, KS 10

| Technical Data | KS 6 NEW | KS 8 | KS 10 |
|------------------------------|-----------------------|-----------------------|-----------------------|
| Crimp force (kN/Ton) | 500/50 | 800/80 | 1,800/180 |
| No grease: 20% less friction | ✓ | ✓ | ✓ |
| Control | Control C.2 | Control C.2 | Control C.2 |
| Max. Crimp range | 55 mm | 139 mm | 139 mm |
| Opening | +27.5 mm | +45 mm | +45 mm |
| Opening without dies | 91.5 mm | 190 mm | 190 mm |
| Type of dies | PBK 266 | PBK 237 | PBK 237 |
| Speed (mm/sec) | | | |
| Close | 12 | 7 | 3.5 |
| Crimp | 12 | 7 | 3.5 |
| Open | 30 | 15 | 6 |
| Noise level | 58 dBA | 58 dBA | 58 dBA |
| Drive | 5.5 kW 3 VAC | 5.5 kW 3 VAC | 5.5 kW 3 VAC |
| Oil | 80 l | 80 l | 80 l |
| L x W x H (mm) | 1,000 x 1,000 x 1,700 | 1,000 x 1,000 x 1,700 | 1,000 x 1,000 x 1,700 |
| Weight | 470 kg | 570 kg | 570 kg |

| Type of dies | |
|--------------|-----|
| PBK 266 | |
| Ø mm | mm |
| 6.8 | 3 |
| 8 | 3 |
| 9 | 3 |
| 10 | 3 |
| 11 | 3 |
| 12 | 3 |
| 14 | 4 |
| 16 | 4 |
| 17 | 4 |
| 19 | 4 |
| 20 | 4.5 |
| 22 | 4.5 |
| 24 | 4.5 |
| 25 | 4.5 |
| 28 | 5 |
| 30 | 5 |
| 32 | 5 |
| 34 | 5 |
| 36 | 5 |
| 39 | 5 |
| 40 | 5 |
| 44 | 5 |
| 47 | 5 |

| Type of dies | |
|--------------|-----|
| PBK 237 | |
| Ø mm | mm |
| 12 | 3 |
| 14 | 3 |
| 16 | 4 |
| 19 | 4 |
| 22 | 4.5 |
| 24 | 4.5 |
| 26 | 4.5 |
| 28 | 4.5 |
| 32 | 5 |
| 36 | 5 |
| 40 | 5 |
| 44 | 5 |
| 47 | 5 |
| 50 | 5 |
| 54 | 5 |
| 57 | 5 |
| 62 | 5 |
| 67 | 5 |
| 71 | 5 |
| 74 | 5 |
| 78 | 5 |
| 84 | 5 |
| 86 | 5 |
| 90 | 5 |
| 96 | 5 |
| 103 | 5 |
| 106 | 5 |