

RG 2



RG 10



Technical data

	RG 2	RG 10
Drive	Diaphragm pump, 7 bar Air	Diaphragm pump, 7 bar Air
Maximum flow rate	25 l/min	180 l/min
Pressure filter	5 µm	10 µm
Air filter	5 µm	5 µm
Max. air consumption	100 NI/min	250 NI/min
Working range	up to 1 1/4" ID	up to 2" ID
Max. length, depending on bore size	2,5 m / 8 feet	20 m / 65 feet
Tank capacity	38 L	215 L
Working area	350 x 750	800 x 1600
Cleaning agent	Non-toxic and corrosion-free emulsion, water based	Non-toxic and corrosion-free emulsion, water based
L x W x H (mm)	960 x 435 x 940	2000 x 840 x 1050
Weight (empty)	55 kg	160 kg

ACCESSORIES

- Hakapur 21,5 L - RG 2 + RG 10 - concentrated cleaning agent
- PJ_30.10.76 - RG 10 - Pressure filter cartridge 5 µm
- PJ_30.10.60 - RG 10 - Pressure filter cartridge 10 µm
- 600.4 - RG 2 - Filter cartridge 5 µm
- 600.5 - RG 2 - Filter cartridge 12 µm

For high specification water glycol and mineral oil flushing rigs, please refer to page 577.



The best return on Investment since 1972.