

UG 20 SWAGING MACHINE

UG 20 Ecoline



UG 20 Mobileline



Technical data

	UG 20 Ecoline	UG 20 Mobileline
Crimp force (kN / Ton)	190	190
Greased machine	✓	✓
Control	Control A	Control A
SAE R 12 / 4SP* 1 piece fitting	1 1/4"	1 1/4"
SAE R 15 / 4SH* 2 piece fitting	1 1/4"	1 1/4"
SAE R 12 / 4SP* 2 piece fitting	1 1/2"	1 1/2"
Industrial	2"	2"
90° Elbows	1 1/4"	1 1/4"
Max. Crimp range	70mm	70mm
Opening	+ 27mm	+ 27mm
Opening without dies	97mm	97mm
Master dies length	100mm	100mm
Type of dies	239-xx-Ø	239-xx-Ø
Speed (mm/sec) - Close	2.0	1.5
Speed (mm/sec) - Crimp	2.0	0.4
Speed (mm/sec) - Open	7.6	5.7
Noise level	69 dBA	69 dBA
Drive	3 kW	1.8 kW
Oil	35 L	4 L
L x W x H (mm)	600 x 550 x 630	430 x 370 x 440
Weight	150 kg	110 kg
Options		
12 VDC / 24 VDC	-	✓
1 Phase	✓	✓
3 Phase	✓	-

Ø Types of die mm	239-xx-Ø-yy mm
6,8	50
9	50
10	50
12	65
14	65
16	65
17	65
19	65
20	65
22	65
24	65
26	65
28	80
30	80
31	80
32	80
36	80
38	80
39	80
40	80
44	80
47	100
50	100
54	100
57	100
62	100

* According to the fitting.

Package

QDS 239 B QDC 239.5

