

ULTRA 2000 TONNE CRIMPER

INSULATORS & LARGE BORE



HM 12-2000



Technical data

| | HMC 12-2000 |
|--|-------------------------------------|
| Crimp force (ton) | 20,000 / 2000 |
| No grease: 20% less friction | ✓ |
| Control | Control C.2 |
| SAE R15 4SH 1 Piece | 3" |
| SAE R15 4SH 2 Pieces | 3" |
| Industry | 12" |
| 90° Bow | 3" |
| Max. crimp range (mm) with basic dies Crimping | 380 Ø PB +50 |
| Opening without dies | 435 mm |
| Die type | 247, 245, 237 |
| Speed (mm / sec) Close / crimp / open | Upon request, depends on power unit |
| L x W x H (mm) | 2000 x 750 x 2400 |
| Weight of tool | 15,000 kg |

| Ø Types of die | |
|----------------|-----|
| 237 L | |
| Ø mm | mm |
| 54 | 118 |
| 57 | 118 |
| 62 | 118 |
| 57 | 118 |
| 71 | 118 |
| 74 | 118 |
| 78 | 118 |
| 84 | 118 |
| 86 | 118 |
| 90 | 118 |
| 96 | 118 |
| 103 | 118 |
| 106 | 126 |
| 111 | 126 |
| 116 | 126 |
| 121 | 126 |
| 126 | 126 |
| 131 | 126 |

| Ø Types of die | |
|----------------|-----|
| 245 | |
| Ø mm | mm |
| 103 | 130 |
| 106 | 130 |
| 111 | 130 |
| 116 | 130 |
| 121 | 130 |
| 126 | 130 |
| 131 | 130 |
| 136 | 130 |
| 146 | 150 |
| 156 | 150 |
| 170 | 150 |
| 185 | 150 |
| 200 | 150 |

| Ø Types of die | |
|----------------|-----|
| 247 | |
| Ø mm | mm |
| 96 | 130 |
| 106 | 130 |
| 126 | 130 |
| 131 | 130 |
| 136 | 130 |
| 146 | 150 |
| 156 | 150 |
| 170 | 170 |
| 185 | 200 |
| 200 | 200 |
| 215 | 200 |
| 230 | 00 |
| 245 | 200 |
| 260 | 200 |
| 275 | 200 |
| 290 | 200 |
| 305 | 200 |

Standard

CONTROL C
+ Touch



TA (A)
Automatic backstop



Optional Extras (See page 463)



Dies to be ordered separately.



The best return on Investment since 1972.